- The following references were used in compiling the checklists, details, and installation notes and are not cited specifically in the text:
- 15. California Office of the State Architect and California Office of Emergency Services. 1990. *Identification and Reduction of Nonstructural Earthquake Hazards in California Schools*. Sacramento and Oakland: California OSA and OES.
- 16. Reitherman, Robert, and Steve Minor. 1989. Technical Guidelines for Earthquake Protection of Nonstructural Items in Communications Facilities. Oakland: California Office of Emergency Services Earthquake Program.
- 17. Wiss, Janney, Elstner Associates, Inc.

- 1994. Information on Protecting Your Home and Business from Nonstructural Earthquake Damage. Los Angeles: California Office of Emergency Services.
- 18. California Office of the State Architect. 1993. Earthquake Bracing of Water Heaters for Single-Family Homes. Sacramento: California OSA.
- 19. Reitherman, Robert. 1991. Nonstructural Earthquake Protection Manual for Idaho Schools. Boise: Idaho Bureau of Disaster Services.
- 20. Checklist of Nonstructural Earthquake Hazards. Sacramento: California Office of Emergency Services Earthquake Project.

## ANNOTATED BIBLIOGRAPHY

This brief bibliography can direct those who require more detailed information to other bibliographies, such as those contained in the references below, and thus is not meant to be This bibliography includes comprehensive. technical publications and nontechnical publications, both listed in alphabetical order, and also information on several organizations or government agencies with a specific focus on engineering earthquake issues. organizations may be able to help the reader identify more recent publications than those listed here.

### **Technical Publications**

Applied Technology Council. 1992. ATC-29: Proceedings of Seminar and Workshop on Seismic Design and Performance of Equipment and Nonstructural Elements in Buildings and Industrial Structures. Redwood City, Calif.: ATC.

O These proceedings contain papers with performance data, analytical methods, and/or suggested details for many specific items, including elevated tanks, ceilings, fire sprinklers, HVAC ducts and equipment, and computer access floors. Most of these papers also contain extensive reference lists pertinent to each specific topic.

Ayres, J. M., T. Y. Sun, and F. R. Brown. 1973. "Nonstructural Damage to Buildings." In *The Great Alaska Earthquake of 1964: Engineering*. Washington D.C.: National Academy of Sciences.

Ayres, J. M., and T. Y. Sun. 1973. "Nonstructural Damage." In *The San Fernando, California, Earthquake of February* 

9, 1971. Washington, D.C.: National Oceanic and Atmospheric Administration.

O These were the first two comprehensive postearthquake damage analyses devoted to the topic of nonstructural components. The authors are mechanical engineers.

Building Seismic Safety Council. 1992. NEHRP Recommended Provisions for the Development of Seismic Regulations for New Buildings. Part 1--Provisions (FEMA 222), Part 2--Commentary (FEMA 223). Washington, D.C.: FEMA.

• The 1994 edition was in draft form at the time this document went to press.

Building Seismic Safety Council. 1992. NEHRP Handbook for the Seismic Evaluation of Existing Buildings. (FEMA 178). Washington, D.C.: FEMA.

Building Seismic Safety Council. 1992. NEHRP Handbook for the Seismic Rehabilitation of Existing Buildings. (FEMA 172). Washington, D.C.: FEMA.

O Items 4, 5, and 6 are all part of a series of FEMA documents produced by the National Earthquake Hazards Reduction Program (NEHRP). These documents may be obtained without charge by writing to the address listed at the end of this bibliography.

Dowrick, D. J. 1977. Earthquake Resistant Design: A Manual for Engineers and Architects. New York: John Wiley & Sons.

 A comprehensive text, including two chapters on nonstructural issues: "Earthquake Resistance of Services," which concerns mechanical and electrical components, and "Architectural Detailing for Earthquake Resistance." The book has an international perspective with references to many different codes.

Earthquake Engineering Research Institute. 1984. *Nonstructural Issues of Seismic Design and Construction*. Publication No. 84-04. Oakland, Calif.: EERI.

O This is a technical overview based on a workshop sponsored by the National Science Foundation. It includes several technical papers and a discussion of key issues, and it lists many additional references.

International Conference of Building Officials. 1994. *Uniform Building Code*, Volumes 1-3. Whittier, Calif.: ICBO.

O See especially the "Earthquake Regulations." The UBC contains specific requirements for some items, such as steel storage racks. New editions of the UBC are issued every three years. The earthquake regulations are taken almost verbatim from the SEAOC "Blue Book," listed below, which also includes a useful commentary.

McGavin, Gary L. 1981. Earthquake Protection of Essential Building Equipment: Design, Engineering, Installation. New York: John Wiley & Sons.

O A book-length treatment of the subject. Especially appropriate for large, complex projects, such as hospitals or power plants.

Office of the State Architect, Structural Safety Section. 1991. Interpretation of Regulations #IR 23-7, Title 24 California Administrative

Code: Anchorage of Non-Structural Building Components and Hospital Equipment. Sacramento: California OSA.

O The regulations legally pertain only to essential nonstructural items in California hospitals, but the regulations can provide a guide as to anchorage engineering of especially essential items for other types of buildings. The Office of the State Architect has been centrally involved in earthquake code regulations since the 1933 Long Beach earthquake.

Schiff, Anshel J. 1980. Pictures of Earthquake Damage to Power Systems and Cost-Effective Methods to Reduce Seismic Failures of Electric Power Equipment. West Lafayette, Ind.: Purdue Research Foundation.

O This is one of the few works in this subject area that is readable by the nontechnical audience. Engineering appendix and bibliography also included.

Structural Engineers Association of California. 1990. Recommended Lateral Force Requirements and Commentary. San Francisco: SEAOC.

O Also known as the SEAOC "Blue Book." The "Requirements" are adopted almost verbatim into the Uniform Building Code, while the "Commentary" explains the assumptions, limitations, and caveats that must be understood for the regulations to be used intelligently. The Structural Engineers Association of California has been active in the development of seismic code regulations, standards of practice, research, and testing for several decades.

Structural Engineers Association of Northern California. 1993. Fall Seminar: Non-Structural Components-Design and Detailing. San

Francisco: SEAONC.

- O These seminar notes include nine papers on the design and detailing of cladding, interior systems, and mechanical systems. Several of these papers also include extensive reference lists.
- U.S. Department of Defense. 1982. Seismic Design for Buildings. Tri-Service Manual TM 5-809-10. Washington, D.C.: Superintendent of Documents.
- O Commentary and calculation examples are provided; see especially Chapters 9, 10, and 11. Generally parallels the UBC but is written as a design aid rather than a code.
- U.S. Department of Defense. 1986. Seismic Design Guidelines for Essential Buildings. Tri-Service Manual TM 5-809-10-1. Washington, D.C.: Superintendent of Documents.
- O Chapters 6 and 7 cover nonstructural components and nonbuilding structures, respectively. Includes several design examples. (Revised edition by Wiss, Janney, Elstner Associates, Inc., due out in 1995).
- U.S. Department of Defense. 1986. Seismic Design Guidelines for Upgrading Existing Buildings, Tri-Service Manual TM 5-809-10-2. Washington, D.C.: Superintendent of Documents.
- O Portions of Chapter 6, Chapter 9, and the design examples in Appendix G are related to nonstructural items.
- U.S. Department of Veterans Affairs, Office of Construction. 1976. Study to Establish Seismic Protection Provisions for Furniture, Equipment,

and Supplies for VA Hospitals. Washington, D.C.: VA.

O This guide shows typical nonstructural damage inside a hospital and illustrated restraint techniques with cost estimates for a variety of types of hospital equipment and furnishings; it includes a brief engineering appendix. Relevant for buildings other than hospitals, especially if laboratories are present.

Yancey, C. W. C., and A. A. Camacho. 1978. Seismic Design of Building Service Systems: The State of the Art. National Bureau of Standards Technical Note 970. Washington, D.C.: NBS.

O A literature survey and review of present practice, especially with regard to the specific mandatory regulations of building codes. The National Bureau of Standards, a federal bureau, has been involved with earthquake research and postearthquake damage reports.

Rihal, Satwant, Barry J. Goodno, Hiroshi Ito, and Robert Reitherman. 1993. "Nonstructural Elements." In *Design of Low-Rise Buildings Subjected to Lateral Forces*, edited by Ajaya Kumar Gupta and Peter James Moss. Ann Arbor: CRC Press.

O A chapter in a book intended for architects, engineers, building officials, and university professors. Most of this chapter concerns earthquakes rather than wind, and additional references are listed.

Reitherman, Robert, and Steve Minor. 1989. Technical Guidelines for Earthquake Protection of Nonstructural Items in Communications Facilities. Oakland: California Office of Emergency Services Earthquake Program.

Intended for the facilities staffs who install

and maintain telecommunications equipment. Includes simplified design guide for the selection of anchor bolts, drawings of anchorage and bracing details, and installation guidance.

#### **Technical Standards**

The following list of publications includes many of the specific design, fabrication, and/or installation requirements for particular nonstructural items.

American Institute of Steel Construction (AISC). 1989. Manual of Steel Construction: Allowable Stress Design. Ninth Edition.

American Petroleum Institute (API). 1988. Welded Steel Tanks for Oil Storage. API Standard 650.

American Society of Mechanical Engineers (ASME). 1990. Safety Code of Elevators and Escalators. ASME A17.1.

American Society of Mechanical Engineers (ASME). Including addenda through 1993. Code for Pressure Piping. ASME B31.

American Society of Mechanical Engineers (ASME). Including addendum through 1993. Boiler and Pressure Vessel Code.

American Society For Testing and Materials (ASTM). 1991. Standard Specification for the Manufacture, Performance and Testing of Metal Suspension Systems for Acoustical Tile and Layin Panel Ceilings. ASTM C635.

American Society For Testing and Materials (ASTM). 1991. Standard Practice for Installation of Metal Ceiling Suspension Systems for Acoustical Tile and Lay-in Panels. ASTM C636.

American Water Works Association (AWWA).

1984. Welded Steel Tanks for Water Storage. D100.

Ceilings and Interior Systems Construction Association (CISCA). 1991. Recommendations for Direct-Hung Acoustical Tile and Lay-In Panel Ceilings, Seismic Zones 0-2.

Ceilings and Interior Systems Construction Association (CISCA). 1990. Recommendations for Direct-Hung Acoustical Tile and Lay-In Panel Ceilings, Seismic Zones 3-4.

Institute of Electrical and Electronic Engineers (IEEE). 1975. Recommended Practice for Seismic Qualification of Class 1E Equipment for Nuclear Power Generating Stations. IEEE Standard 344.

Manufacturers Standardization Society of the Valve and Fitting Industry (MSS). 1988. Pipe Hangers and Supports: Materials, Design, and Manufacture. SP-58.

National Fire Protection Association (NFPA). 1991. Standard for the Installation of Sprinkler Systems. NFPA-13.

Rack Manufacturers Institute (RMI). 1990. Specification for the Design, Testing, and Utilization of Industrial Steel Storage Racks.

Sheet Metal and Air Conditioning Contractors National Association (SMACNA). 1985. HVAC Duct Construction Standards, Metal and Flexible.

Sheet Metal and Air Conditioning Contractors National Association (SMACNA). 1980. Rectangular Industrial Duct Construction Standards.

Sheet Metal and Air Conditioning Contractors National Association (SMACNA), Sheet Metal Industry Fund of Los Angeles, and Plumbing Industry Council. 1992. Guidelines for Seismic Restraint of Mechanical Systems and Plumbing Piping Systems.

### **Nontechnical References**

California Office of the State Architect and California Office of Emergency Services. 1990. *Identification and Reduction of Nonstructural Earthquake Hazards in California Schools*. Sacramento and Oakland: California OSA and California OES

O Survey forms and drawings of bracing concepts for 27 nonstructural items.

FIMS, Inc., and VSP Associates. 1987. Data Processing Facilities: Guidelines for Earthquake Hazard Mitigation. Sacramento, Calif.: VSP, Inc.

O Intended for owners and operators of data processing facilities (DPF). Contains illustrative material on nonstructural hazards and upgrades for raised floors and mainframe computer systems, as well as components found in buildings in general. Not intended as a self-help guide, but provides DPF manager with a basis for discussing design criteria with an engineer.

Noson, Linda, Todd Perbix, and Padraic Burke. 1989. Safer Schools: Earthquake Hazards, Nonstructural. Olympia, Wash.: Washington Superintendent of Public Instruction.

O Includes background information on earthquakes in Washington, survey checklists, and 32 pages of illustrations of nonstructural hazard reduction measures. Olshansky, Robert B. No date (c. 1992). Reducing Earthquake Hazards in the Central U.S.: Nonstructural Hazards. Memphis, Tenn.: Central United States Earthquake Consortium.

O Prepared for the U.S. Geological Survey by the University of Illinois at Urbana-Champaign, Department of Urban and Regional Planning. Illustrations and explanations of nonstructural damage.

Reid & Tarics Associates. 1982. Seismic Restraint Handbook for Furniture, Equipment, and Supplies. Washington, D.C.: Veterans Administration.

O In addition to detailed administration procedures applicable to VA hospitals, the handbook contains detailed forms for collecting nonstructural survey data and producing cost estimates or lists of required materials and labor. Includes 18 pages of restraint details. Originally intended for use by engineering staffs at VA medical facilities, without the use of outside contractors or additional design/analysis assistance.

Reitherman, Robert. 1989. Nonstructural Earthquake Hazard Mitigation for Hospitals and Other Health Care Facilities. FEMA Publication SM (Student Manual) 370. Washington, DC: FEMA.

O Six chapters devoted to the nonstructural topic, some of them generally applicable and others more specific to hospitals. This is a manual used for a two-day course devoted to earthquake hazard reduction and emergency preparedness for hospital facilities.

### **Organizations**

1. Federal Emergency Management Agency (FEMA); California Office of Emergency Services (OES) Earthquake Program; Central United States Earthquake Consortium (CUSEC).

A wide variety of publications, brochures, checklists, videotapes, and slide sets related to earthquake preparedness and nonstructural hazard mitigation are available from many state and federal agencies. Some of the items are tailored to meet differing needs in particular areas of the United States. Some are tailored for specific types of facilities, such as hospitals, schools, day care centers, nursing homes, or single-family residences. Many are available free of charge.

FEMA has regional offices throughout the country, and most states have an office or department of emergency services that may have similar material. The list below includes only several key agencies.

Federal Emergency Management Agency Mitigation Directorate 500 C Street. S.W. Washington, D.C. 20472

State of California Governor's Office of Emergency Services Earthquake Program 2800 Meadowview Road Sacramento, CA 95832 (Phone 916-262-1800; Fax 916-262-1840)

Central United States Earthquake Consortium 2630 East Holmes Road Memphis, TN 38118 (Phone 901-345-0932; Fax 901-345-0998)

2. The National Center for Earthquake Engineering Research (NCEER) is associated with the State University of New York at

Buffalo. Founded in 1987, NCEER sponsors academic research in earthquake engineering, publishes a quarterly bulletin, and has an extensive list of technical reports available by mail. NCEER also has a bibliographic database called QUAKELINE that covers the literature of earthquake engineering and natural hazards mitigation. The database contained over 24,000 records as of January 1994; approximately 400 additions are made each month. The database is accessible on Internet, through both academic computing services and commercial providers.

National Center for Earthquake Engineering Research State University of New York at Buffalo Red Jacket Quadrangle, Box 610025 Buffalo, NY 14621-0025 (Phone 716-645-3391; Fax 716-645-3399; QUAKELINE Info: Phone 716-645-3377)

3. The Earthquake Engineering Research Institute (EERI) was organized in 1949 as a nonprofit corporation with the objective of reducing the impact of earthquakes by means of seismic studies, inspection of earthquake damage, education, and technology transfer, including conferences and the publication of newsletters, reports, technical papers, and conference proceedings. EERI has members in 47 states and 51 foreign countries, including many practicing engineers, architects, and seismologists, as well as university professors and government personnel. Earthquake Spectra, a monthly publication of EERI, contains articles covering a wide range of topics related to earthquakes. EERI has an extensive publication list that also includes videotapes and annotated slide sets showing examples of damage during many past earthquakes.

Earthquake Engineering Research Institute 499 14th Street Oakland, CA 94612-1902 (Phone 510-451-0905; Fax 510-451-5411) 4. The Earthquake Engineering Research Center (EERC) is associated with the University of California at Berkeley. In addition to the extensive shake table testing program, which has been going on for many years and which has produced hundreds of research reports, EERC has an extensive library of earthquake-related materials and a large collection of earthquake slides, and it publishes a newsletter. EERC reports and slide sets are available for sale.

The National Information Service for Earthquake Engineering (NISEE) distributes computer software for earthquake engineering and is associated with EERC. NISEE also maintains a computer database of information on earthquake engineering, accessible through Internet.

Earthquake Engineering Research Center University of California, Berkeley 1301 South 46th Street Richmond, CA 94804-4698 (Phone 510-231-9554) 5. The Applied Technology Council (ATC) is a nonprofit corporation serving the structural engineering profession. The majority of its publications are related to technical topics in seismic analysis and design, postearthquake damage evaluations, new technological advances in seismic design, and so on. The specific focus of the organization is to provide a link between academic research and professional practice. ATC sponsors several technical workshops each year.

Applied Technology Council
555 Twin Dolphin Drive, Suite 270
Redwood City, CA 94065
(Phone 415-595-1542; Fax 415-593-2320)

# APPENDIX A NONSTRUCTURAL INVENTORY FORM

Facility:	Assumed Intensity:

Priority	Nonstructural	Location	Quantity		Risk		ER	Estimated Upgrade Cost		Notes	
	Item			LS	PL	LF		Per Item	Subtotal		
					,						
·									elika a animakka kanang panang Militara		
e ye ta a ayene ta see too a a					an was piliping an area						
								Total			

LS (Life Safety) PL (Property Loss) LF (Loss of Function) ER (Engineering Required) L (Low) M (Moderate) H (High)

**Inventory Form** 

Facility:	XYZ Office	Assumed Intensity: Severe
-----------	------------	---------------------------

Nonstructural	Location	Quantity		Risk		ER	Estimated Upgrade Cost		Notes	
ltem			LS	PL	LF		Per Item	Subtotal		
	roof	1	Н	Н	М	Х	\$500.00 (estimated)	\$500,00	Sits on springs; no seismic restraints	
Suspended ceiling	throughout	5,000 sq. ft.	Н	Н	Н	Х	\$50.00	\$4,000,00	No diagonal wires	
Water heater	utility room	1	М	М	М	×	\$200.00	\$200.00	Gas fired; no flexible pipe no anchorage	
Tall shelving	storage room	40 lin. ft.	н	М	М	Х	\$20,00	\$800,00	*Low priority, contents not essential; unanchored; 8 ft. high	
Half-height partition	work stations	20 (6' each)	М	М	М		\$10.00	\$1,200,00	Stable layout (has returns)	
Suspended lights	offices	50	Н	М	М		\$50.00 (each)	\$2,500.00	Fixtures just rest loosely on ceiling grid	
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				· · · · · · · · · · · · · · · · · · ·				
			27 107 1000							
							Total	\$9,200.00		
	Item Air conditioner Suspended ceiling Water heater Tall shelving Half—height partition	Item Air conditioner roof  Suspended ceiling throughout  Water heater utility room  Tall shelving storage room  Half-height partition stations	Item  Air conditioner roof 1  Suspended ceiling throughout 5,000 sq. ft.  Water heater utility room  Tall shelving storage 40 room lin. ft.  Half-height partition work 20 stations (6' each)	Item         LS           Air conditioner         roof         1         H           Suspended ceiling         throughout         5,000 sq. ft.         H           Water heater         utility room         1         M           Tall shelving         storage room         40 lin. ft.         H           Half—height partition         work stations         20 M         M           (6' each)         (6' each)         (6' each)	Item         LS         PL           Air conditioner         roof         1         H         H           Suspended ceiling         throughout         5,000 sq. ft.         H         H           Water heater         utility room         1         M         M           Tall shelving         storage room         40 H         H         M           Half—height partition         work stations         20 M         M         M           Stations         (6' each)         M         M	Item         LS         PL         LF           Air conditioner         roof         1         H         H         M           Suspended ceiling         throughout         5,000 sq. ft.         H         H         H         H           Water heater         utility room         1         M         M         M         M           Tall shelving         storage room         40         H         M         M         M           Half—height partition stations         work stations         20         M         M         M	Item         LS         PL         LF           Air conditioner         roof         1         H         H         M         X           Suspended ceiling         throughout         5,000 sq. ft.         H         H         H         X           Water heater         utility room         1         M         M         M         M         X           Tall shelving         storage room         40         H         M         M         X           Half—height partition stations         work stations         20 (6' each)         M         M         M         M	LS   PL   LF   Per Item	Item	

Sample Inventory Form

### APPENDIX B

## CHECKLIST OF NONSTRUCTURAL EARTHQUAKE HAZARDS

### How to Use This Checklist

This checklist is intended to be used in surveying buildings to assess whether the nonstructural elements (electrical, mechanical, architectural, and furniture or contents) pose a danger to the building occupants or are likely to cause financial loss or interruption following an earthquake. The questions in this form have been stated in such a way that a "NO" answer indicates there may be a potential problem with the item. Write "Y" for Yes and "N" for No in the box provided. The list may be used in conjunction with the nonstructural inventory form provided in Appendix A. As an example, a line item in the inventory form should be created for each instance where a question in this form is answered "NO".

BUII	LDING UTILITY SYSTEMS	
	RGENCY POWER-GENERATING PMENT	U3. Diesel fuel tank [See Example U3]
genera U1. G	gency power-generating equipment ally consists of the following components:  Generator  Is the emergency generator adequately secured, especially if mounted on motor vibration isolation springs?  atteries, battery rack [See Example U2]	Is the tank securely attached to the supports?  Are the tank supports braced in both directions?  Is the bracing attached with anchor bolts to concrete walls or foundation pad?  Is the foundation large enough to keep the tank from tipping over or sliding?  Is the wall strong enough to support the tank?
	Are the batteries securely attached to the battery rack?	U4. Fuel line, cooling water lines, exhaust flues
	Is the battery rack cross-braced in both directions?  Does the battery rack have anchor bolts secured to a concrete foundation pad?  Is the foundation large enough to keep the rack from sliding or tipping?	Are these lines attached with flexible connections that are able to accommodate relative movement at junctions to spring-mounted equipment, at building entry and exit points, and at expansion joints within the building?

ELECTRICAL EQUIPMENT	U7. Electrical switchgear				
The emergency power system includes both power-generating equipment and the electrical distribution system:	Is the switchgear properly anchored to the floor or wall?				
U5. Transformers	U8. Electrical bus ducts and primary cable system [See Example U8]				
Are transformers properly anchored to the floor or wall?	Are electrical cables or conduit able to distort at the connections with the equipment or where they cross seismic				
U6. Motor Control Center (MCC)  Are the motor control centers properly anchored to the floor or wall?	joints between buildings?  Are the bus ducts or cable conduits laterally braced?				
	(Caution: Only qualified personnel should open access panels on electrical equipment).				
FIRE DETECTION AND SUPPRESSION SYSTEM  The fire detection and suppression system may include any or all of the following components:	Is the ceiling braced so the ceilings won't break the sprinkler heads?  Are the distribution lines able to accommodate movement where they cross seismic joints between buildings?				
U9. Smoke detectors, fire alarm system, control system for automatic fire doors	U12. Fire water pump				
Are fire and smoke detectors properly mounted?	Is the fire water pump anchored, or is it mounted on vibration isolation springs with additional seismic restraints?				
Is the control equipment for the fire alarm system and automatic fire doors securely anchored?	U13. Emergency water tank or reservoir				
U10. Fire extinguisher or fire hose cabinets [See Example U10]	Is the water tank or reservoir securely attached to its supports?  Are the tank supports braced in both directions?				
Are the fire extinguisher cabinets and/or hose cabinets securely mounted?	Are the supports or braces properly anchored to the foundation?				
Are the fire extinguishers secured with quick-release straps?	U14. Smoke control systems				
U11. Fire sprinklers and distribution lines	Are the fans properly braced and/or anchored?				
Are the fire sprinkler piping components laterally braced?	Are fan control centers securely anchored?				

PROPANE TANKS	U16. Shut-off valve
Propane tanks may be used for backup power, heating, or cooking. These systems include:  U15. Propane tank [See Example U15]	Does the system have an automatic earthquake-triggered shut-off valve?  If the shut-off is manual, is a wrench stored within easy reach?
Is the tank securely anchored to the supports?  Are the tank supports braced in both directions?  Are the supports or braces anchored to a concrete foundation pad?  Is the foundation large enough to keep the tank from sliding or tipping over?	U17. Gas or fuel supply pipe  Are the supply pipes laterally braced?  Do the pipes have flexible connections at the tank that are able to accommodate relative movement?
PLUMBING SYSTEM	U20. Distribution pumps
The plumbing system may include:  U18. Gas-fired water heater or boiler	Are the distribution pumps anchored, or are they mounted on vibration isolation springs with additional seismic lateral restraints?
Are the water heaters or boilers securely anchored to the floor or wall?  Does the gas line have a flexible connection to the water heater that is able to accommodate movement?  U19. Residential water heater [See Examples U19a and U19b]  Are the water heaters securely anchored	U21. Hot and cold water pipes, hot water return, wastewater pipes [See Example U21]  Are the pipes laterally braced at reasonable intervals?  Do the pipes have flexible connections to boilers or tanks that are able to accommodate movement?  Are the distribution lines able to
to the floor or wall?  Does the gas line or electrical conduit have a flexible connection to the water heater that is able to accommodate movement?	accommodate movement where they cross seismic joints between buildings?  Are pipe penetrations through structural walls or framing members large enough to allow for some seismic movement?  Are the pipes free of asbestos insulation that could be damaged by movement in an earthquake?

ELEVATORS, ESCALATORS	U25. Elevator cab and hydraulic elevator equipment (hydraulic systems)			
The transport equipment generally includes:	Are the components of the hydraulic			
U22. Elevator cab	system properly anchored?			
Is the elevator cab properly attached to the guide rails?	U26. Escalator			
U23. Cables, counterweights, and guide rails (for cable-traction systems)  Are the cables installed in such a way that they are protected against misalignment during an earthquake?  Are the counterweights properly attached to the guide rails?  Are the guide rails securely attached to the building?  U24. Elevator motor and motor control cabinets  Are the motor and motor control	Is the escalator control equipment securely anchored?  U27. People mover (moving walkway)  Is the control equipment for the people mover properly anchored?  (Caution: The moving parts or components of these systems need to be evaluated by qualified personnel. Inappropriate seismic restraints may compromise the safe operation of these systems.)			
HEATING, VENTILATING, AIR CONDITIONING (HVAC) SYSTEM  The HVAC system may include any or all of the following components, depending on the size of the facility:  U28. Boilers and furnaces  Are boilers and furnaces securely anchored with adequately sized bolts?  Are furnaces, and furnace or boiler bases, constructed without using unreinforced masonry?	U29. Chillers [See Examples U29a and U29b]  Are chillers securely anchored, or are they mounted on vibration isolation springs with added seismic restraints?  U30. Heat pumps or heat exchangers  or are they mounted on vibration isolation springs with added seismic restraints?			

U31.	Fans, blowers, filters		Suspended room heaters or fans [See aple U35]
L132.	Are fans, blowers, and filters securely anchored, or are they mounted on vibration isolation springs with added seismic restraints?  Air compressors [See Example U32]		Are the suspended room heaters, especially gas-fired ones, laterally braced, and are gas-fired heaters fitted with flexible gas connections?
0021	The compressors (see Example 032)	U36.	Distribution ducts [See Example U36]
U33.	Are air compressors anchored, or are they mounted on vibration isolation springs with added seismic restraints?  Roof-mounted HVAC units  Are the HVAC units securely anchored,		Are the distribution ducts laterally braced?  Are the distribution ducts able to accommodate movement at locations where they cross seismic joints?
	or are they mounted on vibration- limiting springs with added seismic restraints?	U37.	Diffusers [See Example U37]  Are the air distribution grills or diffusers anchored to adequately supported sheet-
U34. units	Wall-mounted room air conditioning		metal ducts or to the ceiling grid or wall?
	Are the air conditioning units securely mounted to the wall or shelf?		Do the diffusers have positive independent support, such as at least two hanger wires per diffuser?
	HANICAL APPENDAGES	U39. flues	Roof-mounted equipment, vents, or
U38.	Small stacks or residential chimneys		Is roof-mounted equipment properly anchored?
_	•	U40.	Solar panels
	Are stacks bolted to the supports or foundation by means of anchor bolts of adequate length and double nuts?		Are the solar panels securely anchored to the roof? Is the piping laterally braced?

ARCHITECTURAL ELEMENTS	
BUILT-IN PARTITIONS  These may include elements of many different materials and construction types:  A1. Permanent block wall partitions (concrete masonry unit, brick, hollow clay tile)  Are block wall partitions reinforced? (Most brick or hollow clay tile walls in pre-1933 California buildings are unreinforced. In other regions, unreinforced masonry elements may be found even in current construction.)	Are concrete masonry unit (CMU) partitions detailed to allow sliding at the top?  A2. Partial- and full-height stud wall partitions [See Examples A2a and A2b]  Are partial-height partitions braced to the structure above the ceiling line?  If partitions function as lateral support for tall shelving or cabinets, are these partitions rigidly attached or braced to the structure above the ceiling line?
CEILINGS AND SOFFITS	A4. Soffits (stucco, gypsumboard, plaster)
A3. Ceilings (acoustic tile, gypsumboard, plaster) [See Example A3]  Does the suspended ceiling have adequate diagonal bracing wires?  Are decorative ceiling panels and/or latticework securely attached?  For plaster ceilings, is the wire mesh or wood lath securely attached to the structural framing above?	Are decorative finishes and/or latticework on beam soffits or beneath exterior eves securely attached, particularly over exits?  For stucco soffits, is the wire mesh or wood lath securely attached to the structural framing above?
LIGHTING  A5. Suspended overhead lighting, fixed or track lighting [See Examples A5a and A5b]  Do the lay-in fluorescent light fixtures have positive support, independent of the ceiling grid, such as at least two diagonally opposite hanger wires per light fixture?	Do pendant or stem light fixtures have safety cables so they will not fall if the fixture sways and breaks the stem connection, or are they braced to prevent swaying?  Are spot lights or track lights securely attached to resist seismic shaking?  A6. Emergency lighting and exit lights
Do chandeliers or other hanging fixtures have safety cables to prevent them from impacting each other or a window?	Are emergency lights and exit lights mounted to protect them from falling off shelf supports?

A7. Primary exit doors  If exit doors are heavy metal fire doors that might jam if the building racks during an earthquake, is there a crowbar or sledgehammer located near the exit to facilitate emergency exiting?  A8. Automatic doors with optical or floor sensors, mechanized roll-up doors  A9. Stairways [See Example A9]  Do steel stairs in multistory buildings have sliding supports at one end that can accommodate interstory displacements?  WINDOWS  A13. Overhead glazing or skylights  A14. Glazing [See Example A12]  A15. Overhead glazing or skylights  A16. Building utilities and architectur finishes along egress routes (piping, ducts, ceilings, light, partitions, etc.)  A16. Building utilities and architectur finishes along egress routes (piping, ducts, ceilings, light, partitions, etc.)  A17. Furniture and/or contents along egres routes (cabinets, shelving, etc.)  A18. Furniture and/or contents along egress routes (cabinets, shelving, etc.)  A19. Stairways [See Example A9]  A11. Furniture and/or contents along egress routes (cabinets, shelving, etc.)  A11. Furniture and/or contents along egress routes (cabinets, shelving, etc.)  A11. Furniture and/or contents along egress routes (cabinets, shelving, etc.)  A11. Furniture and/or contents along egress routes (cabinets, shelving, etc.)  A12. Grain [See Example A9]  A23. Overhead glazing or skylights  A243. Overhead glazing or skylights  A244. Interior glass or glass block partition windows, have safety glass?  A245. A15. Overhead glazing or skylights  A25. A26. A275. A				
If exit doors are heavy metal fire doors that might jam if the building racks during an earthquake, is there a crowbar or sledgehammer located near the exit to facilitate emergency exiting?    A8. Automatic doors with optical or floor sensors, mechanized roll-up doors    Do these doors have a manual override in case of a power outage after an earthquake?    A9. Stairways [See Example A9]				partitions in stairwells been removed,
in case of a power outage after an earthquake?  A9. Stairways [See Example A9]  Do steel stairs in multistory buildings have sliding supports at one end that can accommodate interstory displacements?  WINDOWS  A13. Overhead glazing or skylights  A14. Glazing [See Example A12]  Is it known whether the glazing was designed by an architect/engineer to accommodate lateral movement?  Do large windows, especially storefront windows, have safety glass?  Are the glazed partitions laterally brace.  Are furniture and/or contents along the egress routes sufficiently anchored prevent objects from obstructing the egress route?  Are unanchored furniture and/or contents kept far enough from the exponents kept far enough from the exponents kept far enough from the exponents kept far enough from the exponent of the surface panels and obstruct the doors?  A15. Overhead glazing or skylights  Are transoms (glass panes over door made of safety glass?  Are skylights made of safety glass, is it known whether the glazing assemble was designed by an architect/engineer accommodate the expected seism distortion of the surrounding structure and/or contents along the egress routes  Are unanchored furniture and/or contents along the egress routes sufficiently anchored prevent objects from obstructing the egress routes sufficiently anchored prevent objects from obstructing the egress routes sufficiently anchored prevent objects from obstructing the egress routes sufficiently anchored prevent objects from obstructing the egress routes sufficiently anchored prevent objects from obstructing the egress routes sufficiently anchored prevent objects from obstructing the egress routes sufficiently anchored prevent objects from obstructing the egress routes sufficiently anchored prevent objects from obstructing the egress routes sufficiently anchored prevent objects from obstructing the egress route?  Are transoms (glass panes over door made of safety glass?  Are skylights made of safety glass, is it known whether the glazing assemble was designed by	A8. A	If exit doors are heavy metal fire doors that might jam if the building racks during an earthquake, is there a crowbar or sledgehammer located near the exit to facilitate emergency exiting?  Automatic doors with optical or floor	finish	Building utilities and architectural tes along egress routes (piping, ducts, gs, lights, partitions, etc.)  Are piping, ducts, ceilings, lights, partitions, and other elements braced adequately to prevent falling obstructions
A9. Stairways [See Example A9]  Do steel stairs in multistory buildings have sliding supports at one end that can accommodate interstory displacements?  WINDOWS  A13. Overhead glazing or skylights  A14. Glazing [See Example A12]  Is it known whether the glazing was designed by an architect/engineer to accommodate lateral movement?  Do large windows, have safety glass?  A14. Interior glass or glass block partition  egress routes sufficiently anchored prevent objects from obstructing the egress route?  Are unanchored furniture and/contents kept far enough from the ex so they will not slide and obstruct the doors?  A15. Overhead glazing or skylights  A16. Overhead glazing or skylights  A17. Are transoms (glass panes over door made of safety glass?  A18. Are skylights made of safety glass covered with shatter-resistant film?  Are large panes made of safety glass, is it known whether the glazing assemb was designed by an architect/engineer accommodate the expected seism distortion of the surrounding structure and/contents kept far enough from the ex so they will not slide and obstruct the doors?  A16. Overhead glazing or skylights  Are transoms (glass panes over door made of safety glass?  Are skylights made of safety glass, is it known whether the glazing assemb was designed by an architect/engineer accommodate the expected seism distortion of the surrounding structure and/contents kept far enough from the ex so they will not slide and obstruct the glazing or skylights  A18. Overhead glazing or skylights  Are transoms (glass panes over door made of safety glass?  Are skylights made of safety glass, is it known whether the glazing assemb was designed by an architect/engineer accommodate the expected seism distortion of the surrounding structure and/contents and		in case of a power outage after an		
Note: The term safety glass means tempered, laminated, or wired glass; glass covered with shatter-resistant film; or plastic panels.  Al2. Glazing [See Example A12]  Is it known whether the glazing was designed by an architect/engineer to accommodate lateral movement?  Do large windows, especially storefront windows, have safety glass?  Are transoms (glass panes over door made of safety glass?  Are skylights made of safety glass covered with shatter-resistant film?  Are large panes made of safety glass, is it known whether the glazing assemb was designed by an architect/engineer accommodate the expected seism distortion of the surrounding structure accommodate lateral movement?  Al4. Interior glass or glass block partition  Are the glazed partitions laterally brace	A9. S	Do steel stairs in multistory buildings have sliding supports at one end that can		egress routes sufficiently anchored to prevent objects from obstructing the egress route? Are unanchored furniture and/or contents kept far enough from the exits so they will not slide and obstruct the
laminated, or wired glass; glass covered with shatter-resistant film; or plastic panels.  Al2. Glazing [See Example A12]  Is it known whether the glazing was designed by an architect/engineer to accommodate lateral movement?  Do large windows, especially storefront windows, have safety glass?  Mare skylights made of safety glass covered with shatter-resistant film?  Are large panes made of safety glass, is it known whether the glazing assemb was designed by an architect/engineer accommodate the expected seism distortion of the surrounding structure accommodate lateral movement?  Al4. Interior glass or glass block partition  Are the glazed partitions laterally brace	WINI	oows	A13.	Overhead glazing or skylights
		laminated, or wired glass; glass covered with shatter-resistant film; or plastic panels.  Glazing [See Example A12]  Is it known whether the glazing was designed by an architect/engineer to accommodate lateral movement?  Do large windows, especially storefront		Are skylights made of safety glass or covered with shatter-resistant film?  Are large panes made of safety glass, or is it known whether the glazing assembly was designed by an architect/engineer to accommodate the expected seismic distortion of the surrounding structure?  Interior glass or glass block partitions  Are the glazed partitions laterally braced

	IANENT ORNAMENTATION AND NDAGES: EXTERIOR OR	<b>A18.</b> ]	Exterior lighting
INTE			Are exterior light fixtures properly supported or securely attached to the
	Parapets, cornices, veneer or other ation [See Examples A15a and A15b]		structure?
400011		A19.	Flagpoles
	Are parapets or cornices reinforced and adequately braced?  Do other decorative elements have		Are flagpoles securely attached to the structure?
	positive anchorage to the building?  Does the veneer have positive anchorage to the building?	A20.	Tall sculptures (over about 5 feet)
A16.	Freestanding walls or fences (concrete, brick, or stone) [See Example A16]		Are heavy or sharply pointed sculptures anchored to prevent overturning during an earthquake?  Do hanging sculptures have a safety
	Is it known whether freestanding walls or fences were designed by an architect/engineer to resist lateral forces?		cable to prevent them from swinging excessively or falling?
	Are CMU walls adequately reinforced with vertical bars set in grout-filled cells and horizontal bars embedded in the		Heavy signs or exterior billboards  Example A21]
	mortar joints?  Is it known whether CMU walls or fences were built with adequate foundations to prevent them from tipping over in an earthquake?		Are exterior signs or billboards adequately braced and anchored? Are interior signs securely attached with positive connections?
	Over in an entary	A22.	Clay roof tiles
A17.	Hanging appendages		A alar, most tiles seemed to the most
	Are hanging appendages braced or secured with a safety cable?		Are clay roof tiles secured to the roof with one nail-and-wire connection per tile?

FUI	RNITURE AND CONTENTS	-	
Com	MUNICATIONS EQUIPMENT  munications and emergency nunications systems may include:	C5. I recei	Microwave equipment (antennae, ver, transmitter, etc.)  Is the microwave communications equipment securely braced and/or
<b>C1.</b> 1	Radio and short-wave radio equipment		anchored?
	Is radio equipment restrained to keep it from sliding off shelving or tabletops?	C6. (	Computer networks, data storage
	Telephone, cellular phone, and fax oment		Is computer information vital to operations backed up and stored offsite?
	Is important equipment restrained to keep it from sliding off shelving or tabletops?		Is critical computer equipment securely anchored to supports? Is sensitive computer or communications equipment located out
	Are telephones placed on desktops or counters far enough from the edge that they will not slide and fall off?		of range of fire sprinkler heads or joints in the sprinkler pipes where they are less prone to water damage if the sprinkler lines break?
C3. I	Public address system		sprinkler mics break:
	Is the public address system restrained to prevent the equipment from sliding and falling off the shelving?		Wall-mounted televisions or illance cameras
	uspended speakers in conference room		Are wall-mounted televisions or surveillance cameras in elevated locations securely anchored to support shelves or brackets that are in turn
	Are sound system speakers in elevated locations anchored to the structure or hung with safety cables?		adequately connected to the wall?

	CE AND COMPUTER EQUIPMENT	C10. Desktop computer equipment or printers [See Example C10]	
equipm C8. La [See E.	arge computer equipment, tape drives example C8]  Are computers, tape racks, and associated equipment that is about twice as tall as wide, anchored, tethered, and/or braced?  Is heavy computer equipment anchored to the structural floor slab and braced independently of the computer access floors?  Is computer cabling  Is computer cabling long enough to accommodate lateral movement within the building?	Are computer monitors anchored desktops or computers?  Are desktop computers and printer mounted with positive restraint, in on high-friction rubber pads, or I far enough from the edges of destables to prevent them from sliding falling in an earthquake?  C11. Computer access floors [See Notes with Example C8]  Are computer access floors brace diagonal steel members, or is it verified that the vertical pedestals seismically qualified model, instantant accordance with the manufacturer recommendations?  Do cable openings in the access thave edge guards to prevent equilegs from sliding into the opening	ers resting located located located located with s are a led in r's floor ipment
STOR	AGE OF RECORDS AND SUPPLIES	C13. Tall vertical or lateral file cabine	ets
	e for files, accounting records, and ency supplies may include:	[See Example C13]  Do the file cabinet drawers or do latch securely?	ors
	Bookshelves and library stacks 5 feet er [See Examples C12a, C12b, C12c]	Are tall file cabinets anchored wall brackets to a solid wall or s anchored to the floor, or bolted to	tud,
	Are bookshelves properly anchored with brackets to a solid wall or stud, or anchored to the floor?  Are bookshelves fitted with edge restraints or elastic cords to keep books from falling?  Are large and heavy books located on the lowest shelves?  Are rare books given extra protection to prevent falling and water damage?	or more adjacent cabinets to form more stable configuration, i.e., a "footprint"?  Are unanchored cabinets located they will not fall or slide and blo exit?	n a larger so that

C14.	Tall storage racks or shelving		Emergency supply cabinet (water, cine, food, etc.)
	Are tall storage racks or shelves securely anchored to the floor or walls?  Are heavily loaded racks or shelves braced in both directions?  For racks significantly taller than wide, are large anchor bolts used to anchor each leg to a concrete slab?  Are breakable items secured to the shelves or racks, or are they stored in stable units (e.g., are they shelved in the original packing boxes, or are small items shrinkwrapped together)?		Is the cabinet in an accessible location that is not likely to be heavily damaged?  Is the cabinet properly braced and anchored, and are the cabinet doors securely latched?  Especially valuable and fragile handise  Are valuable or fragile items protected against tipping over or falling off shelving or pedestals?
These follow ovens ovens refrige dryers	facilities may include any or all of the ving items: gas and/or electric stoves and built-in or countertop microwave garbage compactors, dishwashers, erators and freezers, clothes washers and ironing and pressing equipment.  Large kitchen or laundry equipment  Are all of the these items securely anchored to the floor, wall, or	labor	Drawer and cabinet latches (kitchen, atory, office, etc.) [See Example C19]  Are the drawers and cabinet doors latched securely, e.g., with special latches or baby-proof hardware that will not fly open in an earthquake?  Freestanding wood stove (wood, pellet s-fired) [See Example C20]  Is the stove securely anchored to the hearth or floor framing in a manner.
	Gas and/or electric hook-up  Example C18]  Are the gas or electric hook-up lines able to accommodate movements at the equipment interface and where they cross seismic joints between buildings?		hearth or floor framing in a manner that will not conduct heat to any combustible materials? Is the exhaust flue anchored to the stove, are the flue sections secured together, and is the flue anchored to the wall with some type of thermal radiation shielding?

HAZ	ARDOUS MATERIALS		Are chemicals stored in accordance with manufacturers' recommendations?
Hazar	dous materials may include:		Are incompatible chemicals stored at
(oxyg	Compressed-gas bottles or cylinders en, carbon dioxide (CO <sub>2</sub> ), ammonia) Example C21]		an appropriate distance from one another so that they will not mix if the containers are broken?  Are the chemicals in each cabinet
	Are gas cylinders tightly secured with one chain near the top and one near the bottom, or are they otherwise restrained?		catalogued properly and marked clearly? Are Material Safety Data Sheets (MSDSs) stored in a location separate from the chemicals?
	Are the chains or restraints securely anchored to a wall or counter with screws or bolts rather than clamps?	C23.	Cabinets for hazardous materials
	Chemical, laboratory, or medical ies [See Example C22]		Are cabinets for hazardous materials securely attached to the floor or to a sturdy wall?
	Are chemical supplies secured with	C24.	Asbestos
	shelf lips several inches high, or are they stored in "egg crate" containers in drawers, so that the containers will not overturn or fall and spill?		Has asbestos insulation been removed, or has it been encapsulated to reduce the possibility of damage in an earthquake?
FURN	NITURE, INTERIOR DECORATION		Freestanding half-height movable ions [See Example C27]
restin	Potted plants or indoor landscaping g on shelves above the floor [See ple C28]		Are freestanding partitions braced or arranged in stable layouts?
	Are heavy potted plants on file cabinets or tall shelves restrained to prevent falling?		Miscellaneous furnishings  Example C28]
	Valuable and fragile artwork or ative vases [See Example C26]		Are unanchored furnishings located where they cannot slide or overturn to block corridors or doors?
		C/20	Taskans wanding maskinss
L I	Are valuable or fragile items protected against tipping over and/or falling off	C29.	Lockers, vending machines

#### APPENDIX C

## NONSTRUCTURAL RISK RATINGS

### Explanation of Risk Ratings

The risk ratings that appear in this Appendix are based on the following assumptions:

Life Safety (LS) Risk: Risk of being injured by the item. This does not include the overall impact on life safety systems in a building, such as loss of emergency power in a hospital or loss of fire detection capability. These disruptions of service are covered under Function below.

Property Loss (PL) Risk: Risk of incurring a repair or replacement cost because of damage to the item. This property loss, as used here, includes the cost of fixing a broken pipe but not the indirect cost of water leakage damage, and includes the cost of repairing a computer but not the loss of business revenue computer downtime might cause. These indirect effects cannot be estimated here on a generic basis.

Loss of Function (LF) Risk: Risk that the item will not function because it has been damaged. This includes some consideration of the impact of this loss of function of the component on the operation of an ordinary occupancy building. Not included are off-site functional impacts, such as the loss of function of a piece of equipment because of a city-wide power outage. Outages of power, water, and other utility company or agency services are real problems to consider but are outside the scope of the item-by-item ratings here.

Unanchored, unbraced items are assumed. The risk ratings are based on the assumption that the item has been installed without seismic bracing, anchorage, restraint, or allowance for differential movements. In areas of the U.S. where seismic building code provisions have

only recently been enforced, this assumption will be generally true. In areas of the western U.S. where seismic codes have been enforced for some time, this assumption may not always be true. Particularly in buildings constructed in the western states since the mid-1970s, some nonstructural items may be anchored or braced, but the assumption of unanchored and unbraced items will still be true for many items on these lists.

The item is assumed to be located at or near the ground level, or in a low-rise building. The most common case of a relatively stiff lowrise building with structural walls is presumed in the ratings here. Items such as full-height partitions and glazing are more likely to be damaged in flexible buildings that experience large lateral deformations. Damage to items sensitive to imposed deformation will be greater in buildings or portions of buildings that are more flexible, such as mid-rise and high-rise buildings; flexible frame buildings without significant structural walls; "soft stories" of buildings with structural walls in most stories but with a story, typically the ground story, that is much less laterally stiff because of the absence of walls; the "soft wall" sides of bearing wall buildings where there is little or no solid wall area, such as the face of a typical commercial storefront building.

A building of ordinary occupancy is assumed. Some nonstructural items in special facilities would be rated differently. For example, shelving in an ordinary occupancy building is assumed here, but the same shelving would be rated quite differently with regard to Life Safety risk in a lab, Property Loss risk in a museum, or risk of Loss of Function in a communications center.

## NONSTRUCTURAL RISK RATINGS

		SH	LS	PL	LF	ER	PG
	UTILITY SYSTEMS	•	•			·	•
	EMERGENCY POWER-GENERATING	EQUIPM	ENT				
U1	Generator	Light	L	L	M	yes	
		Mod	L	M	Н		•
		Severe	L	Н	Н		
U2	Batteries and battery rack	Light	L	L	L	yes	30
		Mod	L	Н	M		
		Severe	L	Н	Н		
U3	Diesel fuel tank	Light	L	L	L	yes	31
		Mod	Н	Н	L		
		Severe	Н	Н	M		
U4	Fuel line	Light	L	L	L		
		Mod	Н	Н	L		
		Severe	Н	Н	M		
	ELECTRICAL EQUIPMENT						
U5	Transformers	Light	<sup>'</sup> L	L	L	yes	
		Mod	L	L	L		
		Severe	M	M	M		
U6	Motor control center (MCC)	Light	L	L	L	yes	
		Mod	L	L	L		
		Severe	M	M	M		

Type of Risk

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
U7	Electrical switchgear	Light	L	L	L	yes	
		Mod	L	L	L		
		Severe	M	M	M		
U8	Electrical bus ducts and primary cable	Light	L	L	L	yes	32
	system	Mod	L	M	M		
		Severe	M	M	M		
	FIRE DETECTION AND SUPPRESSION	SYSTE	M				
U9	Smoke detectors, fire alarm system,	Light	L	L	L		
	control for automatic fire doors	Mod	L	L	L		
		Severe	L	L	L		GODBANI
U10	Fire extinguisher or fire hose cabinets	Light	L	L	L		33
		Mod	M	H	L		
		Severe	M	Н	L		
U11	Fire sprinklers and distribution lines	Light	Ŀ	M	M	yes	
		Mod	L	Н	Н		
		Severe	M	Н	Н		
U12	Fire water pump	Light	L	L	L	yes	
		Mod	L	L	L		
		Severe	M	M	L		
U13	Emergency water tank or reservoir	Light	L	L	L	yes	
		Mod	M	Н	L		,
		Severe	H	Н	L		

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
U14	Smoke control systems	Light	L	L	L	yes	
		Mod	L	M	L		
		Severe	L	M	L		
	PROPANE TANKS						
U15	Propane tank	Light	L	L	L	yes	34
		Mod	Н	Н	M		
		Severe	Н	Н	M		
U16	Shut-off valve	Light	L	L	L		
	·	Mod	H	Н	M		
		Severe	Н	Н	M		
U17	Gas or fuel supply pipe	Light	L	L	L		
		Mod	Н	Н	M		
		Severe	H	Н	M	<u> </u>	
	PLUMBING SYSTEM						
U18	Gas-fired water heater or boiler	Light	Ĺ	L	L	yes	
		Mod	L	L	L		
		Severe	M	M	M		
U19	Residential water heater	Light	L	L	L		35, 36
		Mod	M	Н	L		
		Severe	M	Н	L		
U20	Distribution pumps	Light	L	L	L	yes	
		Mod	L	M	L		
		Severe	L	M	M		

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
U21	Hot and cold water pipes, hot water	Light	L	L	L	yes	37
	return, wastewater pipes	Mod	M	M	M		
		Severe	M	M	M		
	ELEVATORS, ESCALATORS		,	_			
U22	Elevator cab	Light	L	L	L	yes	
		Mod	L	M	M		
		Severe	M	M	M		
U23	Cables, counterweights and guide rails	Light	L	L	L	yes	
	(for cable-traction system)	Mod	Н	M	M		
		Severe	Н	M	M		
U24	Elevator motor and motor control cabinets	Light	L	L	L	yes	
		Mod	L	M	M		
		Severe	L	Н	M		
U25	Elevator cab and hydraulic elevator	Light	L	Ŀ	L	yes	
	equipment (hydraulic systems)	Mod	L	M	M		
		Severe	M	M	M		
U26	Escalator	Light	L	L	L	yes	
		Mod	L	М	L		
		Severe	L	М	L		
U27	People mover (moving walkway)	Light	L	L	L	yes	
		Mod	L	L	L		
		Severe	L	M	L		

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
	HEATING, VENTILATING, AIR COND	ITIONIN	G (H	VAC)	SYST	TEM	
U28	Boilers and furnaces	Light	L	L	L	yes	
		Mod	L	L	L		
	-	Severe	M	M	M		
U29	Chillers	Light	L	L	L	yes	38, 39
		Mod	Ĺ	L	L		
٠		Severe	L	M	M		•
U30	Heat pumps or heat exchangers	Light	L	L	L	yes	
		Mod	L	L	L		
		Severe	L	M	M		
U31	Fans, blowers, filters	Light	L	L	L	yes	
		Mod	L	M	L		÷
		Severe	L	M	M		
U32	Air compressors	Light	L	L	L	yes	40
		Mod	L	M	L		
		Severe	L	M	M		
U33	Roof-mounted HVAC units	Light	L	M	Ĺ	yes	
		Mod	L	M	L		
		Severe	M	Н	M		
U34	Wall-mounted room air conditioning units	Light	L	L	L		
		Mod	Н	M	L		
		Severe	Н	M	L		
U35	Suspended room heaters or fans	Light	L	L	L	yes	41
		Mod	Н	Н	L		
		Severe	Н	Н	L		

Risk Rating

SH= Shaking intensity ER= Engineering required PG= Upgrade detail page number LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
U36	Distribution ducts	Light	L	L	L	yes	42
		Mod	L	L	L		
		Severe	M	M	L		
U37	Diffusers	Light	L	L	L		43
		Mod	Н	Н	L		
:		Severe	Н	Н	L		
	MECHANICAL APPENDAGES		-				
U38	Small stacks or residential chimneys	Light	L	L	L	yes	44
		Mod	M	M	L		
		Severe	Н	M	M		
U39	Roof-mounted equipment, vents or flues	Light	L	L	L	yes	
		Mod	L	M	L		
		Severe	M	M	M		
U40	Solar panels	Light	L	L	L	yes	
		Mod	L	L	L		
		Severe	M	M	L		
							-

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
	ARCHITECTURAL ELEMENTS						
÷	PARTITIONS AND CEILINGS			-			
A1	Permanent block wall partitions (CMU,	Light	L	L	L	yes	
	brick, hollow clay tile)	Mod	H	Н	H		
		Severe	H	Н	H		
A2	Partial- and full-height stud wall partitions	Light	L	L	L	yes	45, 46
		Mod	M	M	Н		
		Severe	M	Н	Н		
A3	Ceilings (acoustic tile, gypsumboard,	Light	L	L	L	yes	47
	plaster)	Mod	M	M	M		
		Severe	Н	Н	Н		
A4	Soffits (stucco, gypsumboard, plaster)	Light	L	L	L		
		Mod	M	M	M		
		Severe	Н	Н	Н	:	
	LIGHTING						
A5	Suspended overhead lighting, fixed or track lighting	Light	L	L	L		48, 49
		Mod	Н	L	L		
		Severe	Н	M	М		
A6	Emergency lighting and exit lights	Light	L	L	L		
		Mod	M	L	L		
		Severe	Н	M	L		
-							

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
	DOORS AND EGRESS ROUTES					<u> </u>	<u>'</u>
A7	Primary exit doors	Light	L	L	L	yes	
:		Mod	L	L	L		•
		Severe	M	М	М		
A8	Automatic doors with optical or floor	Light	L	L	L	yes	
	sensors, mechanized roll-up doors	Mod	L	М	L		
		Severe	M	M	М		
A9	Stairways	Light	L	L	L	yes	50
		Mod	Н	M	L		
		Severe	H	M	H		
A10	Building utilities and architectural finishes	Light	L	L	L	yes	
	along egress routes (ceilings, lights, partitions, etc.)	Mod	Н	M	L		
		Severe	Н	M	L		
A11	Furniture and/or contents along egress	Light	L	L	L		
	routes (cabinets, shelving, etc.)	Mod	Н	M	L		· ·
		Severe	Н	M	L	•	
	WINDOWS						
A12	Glazing	Light	L	L	L	yes	51
		Mod	M	M	L		
		Severe	Н	M	M		
A13	Overhead glazing or skylights	Light	L	L	L	yes	
		Mod	Н	M	L		
		Severe	Н	M	M		

Risk Rating

SH= Shaking intensity ER= Engineering required PG= Upgrade detail page number LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
A14	Interior glass or glass block partitions	Light	L	L	L	yes	
		Mod	M	M	L		
		Severe	Н	Н	M		
	PERMANENT ORNAMENTATION ANI EXTERIOR	APPEN	DAGI	ES : I	NTER	IOR (	OR
A15	Parapets, cornices, veneer or other decoration	Light	M	M	L	yes	52, 53
		Mod	Н	Н	L		
		Severe	Н	Н	L		
A16	Freestanding walls or fences (concrete,	Light	L	L	L	yes	54
	CMU, brick, or stone	Mod	L	L	L		
		Severe	Н	Н	M		
A17	Hanging appendages	Light	L	L	L	yes	
		Mod	Н	Н	L		
		Severe	Н	Н	M		
A18	Exterior lighting	Light	L	L	L		
į		Mod	M	L	L		
		Severe	M	M	M		
A19	Flagpoles	Light	L	L	L	yes	
		Mod	L	L	L		-
		Severe	M	M	L		
A20	Tall sculptures (over 5 feet)	Light	L	L	L	yes	
		Mod	M	M	L		
		Severe	Н	Н	L		

Risk Rating

SH= Shaking intensity ER= Engineering required PG= Upgrade detail page number LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
A21	Heavy signs or exterior billboards	Light	L	L	L	yes	55
		Mod	Н	Н	L		
		Severe	Н	H	L		
A22	Clay roof tiles	Light	L	L	L	yes	
		Mod	L	M	L		
		Severe	M	Н	M		
				-			
	FURNITURE AND CONTENTS						
						-	
	COMMUNICATIONS EQUIPMENT	<del>, :</del>	<del> </del>	1			
C1	Radio and short-wave radio equipment	Light	L	L	L		
		Mod	L	Н	Н		
		Severe	L	Н	Н		
C2	Telephone, cellular phone and fax	Light	L	L	L		
	equipment	Mod	L	Н	M		
		Severe	L	H	M		
C3	Public address system	Light	L	L	L		
		Mod	L	H	L		
		Severe	L	Н	L		
C4	Suspended speakers in conference room or	Light	L	L	L	yes	
	auditorium	Mod	M	M	L		
		Severe	Н	Н	L		
C5	Microwave equipment (antennae, receiver,	Light	L	L	L	yes	
	transmitter, etc.)	Mod	L	M	L		
	•	Severe	M	Н	M		*

Risk Rating

SH= Shaking intensity ER= Engineering required PG= Upgrade detail page number LS= Life safety
PL= Property loss
LF= Loss of function

		GT.	10	TD T	T 10	ER	PG
		SH	LS	PL	LF	ŁK	PG
C6	Computer networks, data storage	Light	L	L	L		
		Mod	L	M	H		:
		Severe	L	Н	H		
C7	Wall-mounted televisions or surveillance	Light	L	L	L	yes	
	cameras	Mod	Н	H	L	·	
		Severe	Н	Н	L		
	OFFICE AND COMPUTER EQUIPMEN	T					
C8	Large computer equipment, tape drives	Light	L	L	L		56
		Mod	L	M	M		
		Severe	M	Н	M		
C9	Computer cabling	Light	L	L	L		
		Mod	L	L	L		
	· ·	Severe	L	L	L		
C10	Desktop computers or office equipment	Light	L	L	L		57
		Mod	L	Н	M		
		Severe	L	Н	M		
C11	Computer access floors	Light	L	L	L	yes	56
		Mod	L	L	M		
-		Severe	L	M	M		
	STORAGE OF RECORDS AND SUPPL	IES					
C12	Book shelves, library stacks (over 5 feet)	Light	L	L	L	yes	58, 59,
ļ			-	<del> </del>	<u> </u>		60
		Mod	H	M	M	-	
		Severe	H	M	M		<u></u>

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
C13	Tall vertical or lateral file cabinets	Light	L	L	L	yes	61
-		Mod	M	М	M	J 0.5	
		Severe	Н	M	М		
C14	Tall storage racks or shelving	Light	L	L	L		
		Mod	Н	М	М		
		Severe	М	М	L		
C15	Emergency supply cabinet (water,	Light	L	L	L		
	medicine, food, etc.)	Mod	L	L	L		
		Severe	M	М	М		A Commonweal
C16	Especially valuable and fragile	Light	L	M	L		
	merchandise	Mod	L	H	L		
		Severe	L	Н	L	·	
	KITCHEN AND LAUNDRY EQUIPMEN	Т				-	
C17	Large kitchen or laundry equipment	Light	L	L	L		
		Mod	M	M	L		
		Severe	Н	M	M		
C18	Gas and/or electric hook-up	Light	L	L	L		62
		Mod	М	Н	Н		
		Severe	Н	Н	Н		
C19	Drawer and cabinet latches (kitchen,	Light	L	L	L		63
	laboratory, office, etc)	Mod	L	L	L		
		Severe	L	M	M		

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
C20	Freestanding wood stove (wood, pellet, or	Light	L	L	L		64
	gas-fired)	Mod	L	L	L		
		Severe	M	M	M		
	HAZARDOUS MATERIALS	_					
C21	Compressed-gas bottles or cylinders	Light	L	L	L		65
	(oxygen, CO <sub>2</sub> , ammonia, etc.)	Mod	M	M	L		
		Severe	Н	M	M		
C22	Chemical, laboratory, or medical supplies	Light	Ļ	L	L	yes	66
		Mod	Н	M	L		
	·	Severe	Н	M	M		
C23	Cabinets for hazardous materials	Light	L	L	L	yes	
		Mod	Н	M	Н		
	·	Severe	Н	M	Н		
C24	Asbestos	Light	L	M	M		
		Mod	L	Н	H		
		Severe	L	Н	Н		
	FURNITURE, INTERIOR DECORATIO	N				·	, . <u> </u>
C25	Potted plants or indoor landscaping resting	Light	L	L	L		69
	on shelves above the floor	Mod	L	L	L		
		Severe	M	L	L		
C26	Valuable and fragile artwork or decorative	Light	L	L	L		67
	vases	Mod	L	H	L		
		Severe	L	H	L		

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

		SH	LS	PL	LF	ER	PG
C27	Freestanding half-height movable	Light	L	L	L		68
	partitions	Mod	L	L	L		
		Severe	M	M	M		
C28	Miscellaneous furnishings	Light	L	L	L		69
		Mod	L	M	L		
		Severe	L	M	L		
C29	Lockers, vending machines	Light	L	L	L		
		Mod	Н	M	L		_
		Severe	Н	M	L		

Risk Rating

SH= Shaking intensity
ER= Engineering required
PG= Upgrade detail page number

LS= Life safety
PL= Property loss
LF= Loss of function

